



Application

Floodlight is designed to illuminate building facade, building security, indoor and outdoor stadiums, monuments, statues, exhibition halls, shopping centers, showrooms, display areas, residences, etc.

Specification

Housing	Die-cast aluminium housing
Front Cover	Tempered glass
Finishing	Black
Dimension	308x82x359mm.
Weight	4.6kg
Power	40/60/80W
Colour Temperature	3000/4000/5700K
CRI	>80
SDCM	3 Step
Luminaire Output	40W : 5400/5400/5400lm 60W : 7800/7800/7800lm 80W : 9600/9600/9600lm
Beam Angle	15/30/30x60(P10) degree 65x120(P10)/65x120(P55) degree
Control Gear	Integral driver
Dimming Method	DMX
Power Supply	220Vac
IP Rating	66
Luminaire Lifetime	50000hrs

Ordering Data

Model	Watt
SLS396/BK-40W-3000K-15D	40W
SLS396/BK-40W-3000K-30D	40W
SLS396/BK-40W-3000K-30x60D(P10)	40W
SLS396/BK-40W-3000K-65x120D(P10)	40W
SLS396/BK-40W-3000K-65x120D(P55)	40W
SLS396/BK-60W-3000K-15D	60W
SLS396/BK-60W-3000K-30D	60W
SLS396/BK-60W-3000K-30x60D(P10)	60W
SLS396/BK-60W-3000K-65x120D(P10)	60W
SLS396/BK-60W-3000K-65x120D(P55)	60W
SLS396/BK-80W-3000K-15D	80W
SLS396/BK-80W-3000K-30D	80W
SLS396/BK-80W-3000K-30x60D(P10)	80W
SLS396/BK-80W-3000K-65x120D(P10)	80W
SLS396/BK-80W-3000K-65x120D(P55)	80W

