

LED Bollard



TIS BLL903

Application

Bollard luminaire is designed to illuminate walkways, steps, low planted areas, pedestrian areas, etc.

Specification

Housing	Die-cast aluminium
Finishing	Powder coated in black
Lens	Polycarbonate
Gasket	Silicone rubber
Dimension	Dia. 180x260/600/900 mm.
Mounting	Surface
Power	BLL903-0.26M : 6W BLL903-0.6M : 10/15/24W BLL903-0.9M : 10/15/24W

Light Source

LED Module

Colour Temperature

3000/4000/5700K
6W : 520 lm (S), 380 lm (A)
10W : 760 lm (S), 630 lm (A)
15W : 1110 lm (S), 880 lm (A)
24W : 1770 lm (S)

Beam Angle

Symmetrical (S)
Asymmetrical (A)

Control Gear

Built-in driver

Power Supply

220-240VAC, 50Hz

Insulation Class

I

IP Rating

66

Luminaire Lifetime

50,000 hrs.

Equivalent

6W : CFL 13W
10W : CFL 18W
15W : CFL 2x18W
24W : MH 35W

Ordering Data

Model	Watt
BLL903-6LED-0.26M	6W
BLL903-10LED-0.6M	10W
BLL903-10LED-0.9M	10W
BLL903-15LED-0.6M	15W
BLL903-15LED-0.9M	15W
BLL903-24LED-0.6M	24W
BLL903-24LED-0.9M	24W

