

LED Recessed Downlight

TIS RAL135J

Application

Recessed downlight is designed to use for office buildings, shopping centers, convenience stores, modern trade stores, discount stores, hotels, restaurants, residences, recreation centers, museums, etc.

Specification

Housing Die-cast Aluminum
Description Primary reflector : Vacuum aluminum plating PC.
 4 different secondary reflectors are available for various applications
 MI (front reflector mirror chrome)
 WR (front reflector white)
 BR (front reflector black)
 MB (front reflector mirror black)

Finishing

Mounting

Power

Light Source

Colour Temperature

CRI

Lamp Output

Powder coated in white

Recessed

18/23/30/35/40W

LED COB

3000K/4000K/5000K

>90/ >90/ >80

18W : 2062/2226/2418 lm

23W : 2635/2845/3090 lm

30W : 3500/3770/4015 lm

35W : 3940/4245/4520 lm

40W : 4502/4581/5165 lm

Luminaire Output

18W : 1504/1609/1721 lm *

23W : 2014/2154/2305 lm **

30W : 2745/2937/3142 lm **

35W : 3055/3268/3497 lm **

40W : 3342/3575/3826 lm **

Beam Angle

18W : 10 Degree

23/30/35/40W : 18/26/38/50/65 Degree

UGR

<19

Control Gear

Separate Driver

Power Supply

220-240VAC, 50Hz

Power Factor

>0.9

Insulation Class

I

IP Rating

20

Luminaire Lifetime

40,000 hrs

Remarks


* Value at 10 Degree

** Value at 38 Degree

Ordering Data

Model	Watt
RAL135J/MI/WH-18LED	18W
RAL135J/MI/WH-23LED	23W
RAL135J/MI/WH-30LED	30W
RAL135J/MI/WH-35LED	35W
RAL135J/MI/WH-40LED	40W

Related Products



Honey comb

