

# LED Canopy / Tunnel



TIS RCL436

## Application

Canopy is designed to illuminate tunnels, underpasses, warehouses, garages, indoor gymnasiums, recreational and competition sport fields, etc.

## Specification

<b>Housing</b>	Die-cast aluminium
<b>Front Cover</b>	Clear toughened glass
<b>Finishing</b>	Powder coated in white
<b>Lens</b>	Acrylic (PMMA)
<b>Gasket</b>	Silicone rubber
<b>Dimension</b>	380x582x147 mm.
<b>Cut Out</b>	360x562 mm.
<b>Mounting</b>	Recessed
<b>Power</b>	195W
<b>Light Source</b>	LED Module
<b>Colour Temperature</b>	3000/4000/5700K
<b>Luminaire Output</b>	26325 lm
<b>Beam Angle</b>	90/115 degree Asymmetrical distribution : FW5
<b>Control Gear</b>	Built-in driver
<b>Dimming Method</b>	1-10V (optional)
<b>Power Supply</b>	220-240VAC, 50Hz
<b>Power Factor</b>	>0.95
<b>Insulation Class</b>	I
<b>IP Rating</b>	66
<b>Luminaire Lifetime</b>	50,000 hrs.
<b>Equivalent</b>	MH 400W

## Ordering Data

Model	Watt
RCL436-195LED	195W

