

LED Lamp



TIS LED-T8/STD/CT

Application



This LED lamp is designed to replace conventional lamp which is safe cost and save energy depending on each lamp types. There is no UV,long lifetime,etc.

Specification


| | |
|--------------------|--------------------------------------|
| Housing | High quality plastic |
| Description | Energy saving up to 65% |
| | No UV |
| | Non-dimmable |
| | 830 : 3000K |
| | 840 : 4000K |
| | 865 : 6500K |
| | TIS 1955-2551 and TIS 2779-2562 |
| Power | 9/16W |
| Light Source | LED-SMD |
| Colour Temperature | 3000/4000/6500K |
| Lamp Output | 1050/2000/2100lm |
| | (See.Detail in ordering data) |
| Beam Angle | > 160 degree |
| Control Gear | Built-in driver |
| Power Supply | 220-240VAC,50Hz |
| Protection | 9W, Pf >0.9, CRI>80 and THDi <15% * |
| | 16W, Pf >0.9, CRI>80 and THDi <15% * |
| Lamp Lifetime | 50,000 hrs. |
| Equivalent | T8:18/36W |

Ordering Data


| Model | Watt |
|----------------------------------|------|
| L&E#STD LED-T8-1050LM/830/9W/CT | 9W |
| L&E#STD LED-T8-1050LM/840/9W/CT | 9W |
| L&E#STD LED-T8-1050LM/865/9W/CT | 9W |
| L&E#STD LED-T8-2100LM/865/12W/CT | 12W |
| L&E#STD LED-T8-2000LM/830/16W/CT | 16W |
| L&E#STD LED-T8-2100LM/840/16W/CT | 16W |
| L&E#STD LED-T8-2100LM/865/16W/CT | 16W |



Related Products



Recessed Luminaire



Recessed Luminaire *



Surface Luminaire



Pendant Luminaire

WIRING Diagram

