

LED Recessed Linear



TIS RBPL300/UGR19

Application

This luminaire is designed to use for office buildings, schools, storage areas, hospitals, and other working areas where is required highly uniformity illumination, etc.

Specification


Housing	Extruded aluminium
Finishing	Powder coated in white
Diffuser	Opal
Mounting	Recessed T-bar (for Concealed ceiling recommend to use additional frame)
Power	RBPL300/UGR19/S : 18W RBPL300/UGR19/L : 36W
Light Source	LED Module
Colour Temperature	4000/6500K
Luminaire Output	RBPL300/UGR19/S : 2000/2000 lm RBPL300/UGR19/L : 4000/4000 lm
UGR	<19
Control Gear	Separate driver
Power Supply	220-240VAC, 50Hz
Power Factor	>0.9
Insulation Class	I
IP Rating	20
Luminaire Lifetime	50,000 hrs.
Equivalent	RBPL300/UGR19/S: T5 2x14W/T8 2x18W RBPL300/UGR19/L: T5 2x28W/T8 2x36W

Ordering Data


Model	Watt
RBPL300/UGR19/S-18LED	18W
RBPL300/UGR19/L-36LED	36W



RBPL300/UGR19/S



RBPL300/UGR19/L



Related Products



Concealed Ceiling Frame
300x600mm.



Concealed Ceiling Frame
300x1200mm.

