

LED Clean Room



TIS LRCRM600/FO/CT

Application



Clean room is designed for unique application which is require limitation of dust such as food processing areas, control rooms, etc.

Specification

Housing	Die-formed cold roll steel Service method : front opening Sealing : Triple gasketing system
Description	Can use for clean room class 10,000 or higher
Finishing	Powder coated in white
Diffuser	Prismatic (Opal, stipple, clear are available as option)
Mounting	Recessed
Power	2S : 14-18W (2 lamps) 3S : 21-27W (3 lamps) 2L : 28-32W (2 lamps) 3L : 42-48W (3 lamps)
Light Source	LED-T8
Lamp Holder	G13
Colour Temperature	3000/4000/6500K
Lamp Output	2S : L&E : 2x7/8/9W : 2x1050 lm 3S : L&E : 3x7/8/9W : 3x1050 lm 2L : L&E : 2x14/16W : 2x2100 lm 3L : L&E : 3x14/16W : 3x2100 lm
Luminaire Output	2S : 14/16/18W : 1585lm 3S : 21/24/27W : 2380 lm 2L : 28/32W : 3175 lm 3L : 42/48W : 4760 lm
Power Supply	220-240VAC, 50Hz
Insulation Class	I
IP Rating	50
LED Lifetime Equivalent	L&E : 25,000/40,000/50,000 hrs. 14-18W : T5 2x14W/T8 2x18W 21-27W : T5 3x14W/T8 3x18W 28-32W : T5 2x28W/T8 2x36W 42-48W : T5 3x28W/T8 3x36W

Ordering Data

Model	Watt
LRCRM600/FO/2S/CT-XXLED-T8	14-18W
LRCRM600/FO/3S/CT-XXLED-T8	21-27W
LRCRM600/FO/2L/CT-XXLED-T8	28-32W
LRCRM600/FO/3L/CT-XXLED-T8	42-48W



Related Products



LED-T8

