

# LED Pendant



## TIS LPLL105/CT

### Application

Pendant luminaire is designed to use for office buildings, book stores, discount stores, shopping centers, convenience stores, residences, hotels, restaurants, hospitals, etc.

### Specification


<b>Housing</b>	Extruded aluminium
<b>Finishing</b>	Powder coated in grey, white or black
<b>Louver</b>	Matt anodized aluminium
<b>Mounting</b>	Suspension wire
<b>Power</b>	2S : 14-18W (2 lamps) 2L : 28-32W (2 lamps)
<b>Light Source</b>	LED-T8
<b>Lamp Holder</b>	G13
<b>Colour Temperature</b>	3000/4000/6500K
<b>Lamp Output</b>	2S : L&E : 2x7/8/9W : 2x1050 lm 2L : L&E : 2x14/16W : 2x2100 lm
<b>Luminaire Output</b>	2S : 14/16/18W : 1370 lm 2L : 28/32W : 2740 lm
<b>Power Supply</b>	220-240VAC, 50Hz
<b>Insulation Class</b>	I
<b>IP Rating</b>	20
<b>LED Lifetime</b>	L&E : 25,000/40,000/50,000 hrs.
<b>Equivalent</b>	14-18W : T5 2x14W/T8 2x18W 28-32W : T5 2x28W/T8 2x36W
<b>Remarks</b>	Option 1.Box with Transparent Wire 1.5m

### Ordering Data


Model	Watt
LPLL105/2S/CT-XXLED-T8	14-18W
LPLL105/2L/CT-XXLED-T8	28-32W



LPLL105/2S



LPLL105/2L



### Related Products

