

LED Surface Linear



LINE S

Application

This luminaire is designed to use for office buildings, schools, storage areas, hospitals, and other working areas where is required highly uniformity illumination, etc.

Specification


Housing	Extruded aluminium
Finishing	Powder coated in grey, white or black
Diffuser	Acrylic (PMMA)
Mounting	Surface
Power	S60 : 11/14/16/19W S120 : 22/28/32/38W
Light Source	LED Module
Colour Temperature	3000/4000/6500K
Luminaire Output	S60 : 11W : 1150 lm, 14W : 1450 lm S60 : 16W : 1700 lm, 19W : 1950 lm S120 : 22W : 2300 lm, 28W : 2900 lm S120 : 32W : 3400 lm, 38W : 3900 lm
Control Gear	Built-in driver
Power Supply	220-240VAC, 50Hz
Power Factor	>0.9
Insulation Class	I
IP Rating	20
Luminaire Lifetime	30,000 hrs.
Remarks	Option 1. Luminaire connector (Continued)

Ordering Data


Model	Watt
LINE S60-11LED	11W
LINE S60-14LED	14W
LINE S60-16LED	16W
LINE S60-19LED	19W
LINE S120-22LED	22W
LINE S120-28LED	28W
LINE S120-32LED	32W
LINE S120-38LED	38W



LINE S60



LINE S120



Related Products



LINE S/WH




LINE S/BK



LINE SL



LINE ST



LINE SX



Luminaire
connector(continued)



LED Strip Module

