

LED Canopy / Tunnel



TIS RCL435

Application

Canopy is designed to illuminate tunnels, underpasses, warehouses, garages, indoor gymnasiums, recreational and competition sport fields, etc.

Specification

Housing	Die-cast aluminium
Front Cover	Clear toughened glass
Finishing	Powder coated in white
Lens	Acrylic (PMMA)
Gasket	Silicone rubber
Dimension	290x423x143 mm.
Cut Out	270x405 mm.
Mounting	Recessed
Power	55/70/105W
Light Source	LED Module
Colour Temperature	3000/4000/5700K
Luminaire Output	55W : 7700 lm (94/115 degree)
	55W : 6600 lm (FW4)
	70W : 9800 lm (94/115 degree)
	70W : 8400 lm (FW4)
	105W : 14175 lm (94/115 degree)
	105W : 12600 lm (FW4)
Beam Angle	94/115 degree
	Asymmetrical distribution : FW4
Control Gear	Built-in driver
Dimming Method	1-10V (optional)
Power Supply	220-240VAC, 50Hz
Power Factor	>0.95
Insulation Class	I
IP Rating	66
Luminaire Lifetime Equivalent	50,000 hrs.
	55W : MH 100W
	70W : MH 150W
	105W : MH 250W

Ordering Data

Model	Watt
RCL435-55LED	55W
RCL435-70LED	70W
RCL435-105LED	105W

