

LED Post Top



PTL720/RP

Application

Post-top luminaire is designed to use for public or private areas such as hotels, houses, gardens, parks, walkways, etc.

Specification

Housing	Die-cast aluminium with zinc coated steel pole
Finishing	Powder coated in black
Lens	Acrylic (PMMA)
Gasket	Silicone rubber
Dimension	Luminaire : 150x700x70 mm. Pole : Dia.114 mm., H3000-6000 mm.
Mounting	Surface
Power	Single head (/SH) ; 35/70/105W Double head (/DH) ; 70W (2x35W) Double head (/DH) ; 140W (2x70W) Double head (/DH) ; 210W (2x105W)
Light Source	LED Module
Colour Temperature	3000/4000K
Luminaire Output	Single head (/SH) ; 35W : 4900 lm Single head (/SH) ; 70W : 9800 lm Single head (/SH) ; 105W : 13650 lm Double head (/DH) ; 70W : 2x4900 lm Double head (/DH) ; 140W : 2x9800 lm Double head (/DH) ; 210W : 2x13650 lm
Beam Angle	Street lighting distribution : SL9 Forward throw distribution : FW5
Control Gear	Built-in driver
Dimming Method	1-10V (optional)
Power Supply	220-240VAC, 50Hz
Power Factor	>0.95
Insulation Class	I
IP Rating	66
Luminaire Lifetime	50,000 hrs.
Equivalent	35W : MH 70W 70W : MH 150W 105W : MH 250W

Ordering Data

Model	Watt
PTL720/RP/SH-35LED	35W
PTL720/RP/DH-70LED	70W
PTL720/RP/SH-70LED	70W
PTL720/RP/SH-105LED	105W
PTL720/RP/DH-140LED	140W
PTL720/RP/DH-210LED	210W

