

# LED Floodlight / Spotlight



## TIS FLL470

### Application

Floodlight is designed to illuminate building facade, building security, indoor and outdoor stadiums, monuments, statues, exhibition halls, shopping centers, showrooms, display areas, residences, etc.

### Specification

|                           |                                |
|---------------------------|--------------------------------|
| <b>Housing</b>            | Die-cast aluminium             |
| <b>Front Cover</b>        | Clear toughened glass          |
| <b>Finishing</b>          | Powder coated in black         |
| <b>Lens</b>               | Polycarbonate                  |
| <b>Gasket</b>             | Silicone rubber                |
| <b>Dimension</b>          | 590x160x650 mm.                |
| <b>Mounting</b>           | Surface                        |
| <b>Power</b>              | 1000W                          |
| <b>Light Source</b>       | LED Module                     |
| <b>Colour Temperature</b> | 5700K                          |
| <b>Luminaire Output</b>   | 125000/140000/140000/140000 lm |
| <b>Beam Angle</b>         | 13/32/60/90 degree             |
| <b>Control Gear</b>       | Built-in driver                |
| <b>Dimming Method</b>     | 1-10V (optional)               |
| <b>Power Supply</b>       | 220-240VAC, 50Hz               |
| <b>Power Factor</b>       | >0.95                          |
| <b>Insulation Class</b>   | I                              |
| <b>IP Rating</b>          | 66                             |
| <b>Luminaire Lifetime</b> | 50,000 hrs.                    |
| <b>Equivalent</b>         | MH 2000W                       |

### Ordering Data

| Model          | Watt  |
|----------------|-------|
| FLL470-1000LED | 1000W |

