

 TIS SLU209
**Application**

Underwater is designed to illuminate  
aquariums,water falls,swimming pools,  
fountains,etc.

**Specification**

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| <b>Housing</b>            | 316 stainless steel                                         |
| <b>Front Cover</b>        | Tempered glass                                              |
| <b>Description</b>        | Max depth 2 meter<br>Supplied Cable 5 meter(Optional 20 m.) |
| <b>Lens</b>               | tempered glass                                              |
| <b>Dimension</b>          | 180x180x131 mm.                                             |
| <b>Weight</b>             | 2 kg                                                        |
| <b>Body Colour</b>        | stainless steel                                             |
| <b>Power</b>              | 21W                                                         |
| <b>Light Source</b>       | LED module                                                  |
| <b>Colour Temperature</b> | 2700/3000/4000/6500K                                        |
| <b>CRI</b>                | >80                                                         |
| <b>SDCM</b>               | 3 SDCM                                                      |
| <b>Luminaire Output</b>   | 1680/1680/1890/1890lm                                       |
| <b>Beam Angle</b>         | 25/45 degree                                                |
| <b>Control Gear</b>       | Remote driver                                               |
| <b>Dimming Method</b>     | DMX                                                         |
| <b>Power Supply</b>       | 24Vdc                                                       |
| <b>IP Rating</b>          | 68                                                          |
| <b>Luminaire Lifetime</b> | 50000hrs.                                                   |

**Ordering Data**

| Model                            | Watt |
|----------------------------------|------|
| SLU209-V2-21W-3000K-25D          | 21W  |
| SLU209-V2-21W-3000K-25D-Cable20m | 21W  |
| SLU209-V2-21W-3000K-45D          | 21W  |
| SLU209-V2-21W-3000K-45D-Cable20m | 21W  |

