





Material	Extrusion Aluminium housing with pc front cover
Cover Options	Diffused Flat Shape Clear Flat Shape (Option)
Driver	Remote Driver
Life Time	50,000 hours, L70 @ 25°C
Ambient Temperature	-20°C ~ 50°C
IP Rating	66
CRI	≥ 80
Control Options	Monochrome : 1-10V, DALI, DMX (Via Remote Driver) Colorchange : DMX (Via Remote Driver) Dynamic White : DMX (Via Remote Driver)
Weight (kg)	1 kg/m



LD011 (Diffused cover)


Watt (W)	CCT (K)	Beam Angle (°)	Input (V)
1.8W (304mm)	2700K (360lm/m)	110°	24Vdc
3W (504mm)	3000K (378lm/m)		
6W (1004mm)	4000K (415lm/m)		
	6500K (445lm/m)		
3.6W (304mm)	2700K (720lm/m)		
6W (504mm)	3000K (756lm/m)		
12W (1004mm)	4000K (830lm/m)		
	6500K (910lm/m)		
3.6W (304mm)	RGB (336lm/m)		
6W (504mm)			
12W (1004mm)			
6W (304mm)	Dynamic white		
10W (504mm)	2700K-6500K (1260lm/m)		
20W (1004mm)			

LED LINEAR DIFFUSER



LD011 (Clear cover)

Watt (W)	CCT (K)	Beam Angle (°)	Input (V)
1.8W (304mm)	2700K (468lm/m)	110°	24Vdc
3W (504mm)	3000K (491lm/m)		
6W (1004mm)	4000K (540lm/m)		
	6500K (579lm/m)		
3.6W (304mm)	2700K (936lm/m)		
6W (504mm)	3000K (983lm/m)		
12W (1004mm)	4000K (1079lm/m)		
	6500K (1183lm/m)		
3.6W (304mm)	RGB (437lm/m)		
6W (504mm)			
12W (1004mm)			
6W (304mm)	Dynamic white		
10W (504mm)	2700K-6500K (1638lm/m)		
20W (1004mm)			



Accessories



Feeder Cable L = 350 mm