

LED Clean Room



TIS LRCRM300/FO/CT

Application




Clean room is designed for unique application which is require limitation of dust such as food processing areas, control rooms, etc.

Specification

Housing	Die-formed cold roll steel Service method : front opening Sealing : Triple gasketing system
Description	Can use for clean room class 10,000 or higher
Finishing	Powder coated in white
Diffuser	Prismatic (Opal, stipple, clear are available as option)
Mounting	Recessed
Power	2S : 14-18W (2 lamps) 2L : 28-32W (2 lamps)
Light Source	LED-T8
Lamp Holder	G13
Colour Temperature	3000/4000/6500K
Lamp Output	2S : L&E : 2x7/8/9W : 2x1050 lm 2L : L&E : 2x14/16W : 2x2100 lm
Luminaire Output	2S : 14/16/18W : 1525 lm 2L : 28/32W : 3050 lm
Power Supply	220-240VAC, 50Hz
Insulation Class	I
IP Rating	50
LED Lifetime	L&E : 25,000/40,000/50,000 hrs.
Equivalent	14-18W : T5 2x14W/T8 2X18W 28-32W : T5 2x28W/T8 2X36W

Ordering Data

Model	Watt
LRCRM300/FO/2S/CT-XXLED-T8	14-18W
LRCRM300/FO/2L/CT-XXLED-T8	28-32W



Related Products



LED-T8

