

LED Surface Linear



LSLIP/CT

Application

This luminaire is designed to use for office buildings, schools, storage areas, hospitals, and other working areas where is required highly uniformity illumination, etc.

Specification


Housing	Die-formed cold roll steel
Finishing	Powder coated in white
Reflector	Mirror anodized aluminium
Diffuser	Opal Acrylic
Mounting	Surface
Power	2S: 14-18W (2 lamps) 2L: 28-32W (2 lamps)
Light Source	LED-T8
Lamp Holder	G13
Colour Temperature	3000/4000/6500K
Lamp Output	2S: L&E : 2x7/8/9W: 2x1050 lm 2L: L&E : 2x14/16W: 2x2100 lm
Luminaire Output	2S: 14/16/18W : 1338 lm 2L: 28/32W : 2675 lm
Power Supply	220-240VAC, 50Hz
Power Factor	>0.9
Insulation Class	I
IP Rating	40
LED Lifetime	L&E: 25,000/40,000/50,000 hrs.
Equivalent	14-18W: T5 2x14W/T8 2x18W 28-32W: T5 2x28W/T8 2x36W

Ordering Data


Model	Watt
LSLIP/2S/CT-XXLED-T8	14-18W
LSLIP/2L/CT-XXLED-T8	28-32W



LSLIP/2S



LSLIP/2L



Related Products



LED-T8

