

LED Batten



LLBS40/CT

Application

This luminaire is designed to use for convenience stores, discount stores, modern trade stores, factories, schools, storage areas, hospitals, hotels, shopping centers, corridors, industrial areas, car parks, etc.

Specification


Housing	Die-formed cold roll steel
Finishing	Powder coated in white
Mounting	Surface or suspended
Power	1S : 7-9W (1 lamp) 1L : 14-16W (1 lamp) 2S : 14-18W (2 lamps) 2L : 28-32W (2 lamps)
Light Source	LED-T8
Lamp Holder	G13
Colour Temperature	3000/4000/6500K
Lamp Output	1S : L&E : 7/8/9W : 1050 lm 1L : L&E : 14/16W : 2100 lm 2S : L&E : 2x7/8/9W : 2x1050 lm 2L : L&E : 2x14/16W : 2x2100 lm
Luminaire Output	1S : 7/8/9W : 1035 lm 1L : 14/16W : 2068 lm 2S : 14/16/18W : 2070 lm 2L : 28/32W : 4136 lm
Power Supply	220-240VAC, 50Hz
Insulation Class	I
IP Rating	20
LED Lifetime	L&E : 25,000/50,000 hrs.
Equivalent	7-9W : T5 1x14W/T8 1x18W 14-16W : T5 1x28W/T8 1x36W 14-18W : T5 2x14W/T8 2x18W 28-32W : T5 2x28W/T8 2x36W

Ordering Data


Model	Watt
LLBS40/1S/CT-XXLED-T8	7-9W
LLBS40/1L/CT-XXLED-T8	14-16W
LLBS40/2S/CT-XXLED-T8	14-18W
LLBS40/2L/CT-XXLED-T8	28-32W




LLBS40/2S




LLBS40/1S



LLBS40/2L



LLBS40/1L



Related Products



LED-T8

