

# LED Canopy / Tunnel



## TIS CAL511

### Application

Canopy is designed to illuminate tunnels, underpasses, warehouses, garages, indoor gymnasiums, recreational and competition sport fields, etc.

### Specification

|                           |  |
|---------------------------|--|
| <b>Housing</b>            | Die-cast aluminium   |
| <b>Front Cover</b>        | Clear toughened glass  |
| <b>Finishing</b>          | Powder coated in black   |
| <b>Lens</b>               | Acrylic (PMMA)   |
| <b>Gasket</b>             | Silicone rubber  |
| <b>Dimension</b>          | 290x580x180 mm.  |
| <b>Mounting</b>           | Surface  |
| <b>Power</b>              | 105/125/150W   |
| <b>Light Source</b>       | LED Module   |
| <b>Colour Temperature</b> | 3000/4000/5700K  |
| <b>Luminaire Output</b>   | 105W : 15225 lm (55 degree)<br>105W : 14175 lm (90 degree)<br>125W : 17500 lm (55 degree)<br>125W : 16875 lm (90 degree)<br>150W : 19500 lm (55 degree)<br>150W : 18750 lm (90 degree) |
| <b>Beam Angle</b>         | 55/90 degree   |
| <b>Control Gear</b>       | Built-in driver  |
| <b>Dimming Method</b>     | 1-10V (optional)   |
| <b>Power Supply</b>       | 220-240VAC, 50Hz   |
| <b>Power Factor</b>       | >0.95  |
| <b>Insulation Class</b>   | I  |
| <b>IP Rating</b>          | 66   |
| <b>Luminaire Lifetime</b> | 50,000 hrs.  |
| <b>Equivalent</b>         | MH 250W  |

### Ordering Data

| Model         | Watt |
|---------------|------|
| CAL511-105LED | 105W |
| CAL511-125LED | 125W |
| CAL511-150LED | 150W |

