

# LED Recessed Linear



## TIS LRLL105/CT

### Application




This luminaire is designed to use for office buildings, schools, storage areas, hospitals, and other working areas where is required highly uniformity illumination, etc.

### Specification

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| <b>Housing</b>            | Extruded aluminium                                                 |
| <b>Finishing</b>          | Powder coated in white                                             |
| <b>Louver</b>             | Matt anodized aluminium                                            |
| <b>Mounting</b>           | Recessed                                                           |
| <b>Power</b>              | 2S : 14-18W (2 lamps)<br>2L : 28-32W (2 lamps)                     |
| <b>Light Source</b>       | LED-T8                                                             |
| <b>Lamp Holder</b>        | G13                                                                |
| <b>Colour Temperature</b> | 3000/4000/6500K                                                    |
| <b>Lamp Output</b>        | 2S : L&E : 2x7/8/9W : 2x1050 lm<br>2L : L&E : 2x14/16W : 2x2100 lm |
| <b>Luminaire Output</b>   | 2S : 14/16/18W : 1370 lm<br>2L : 28/32W : 2742 lm                  |
| <b>Power Supply</b>       | 220-240VAC, 50Hz                                                   |
| <b>Insulation Class</b>   | I                                                                  |
| <b>IP Rating</b>          | 20                                                                 |
| <b>LED Lifetime</b>       | L&E : 25,000/40,000/50,000 hrs.                                    |
| <b>Equivalent</b>         | 14-18W : T5 2x14W/T8 2x18W<br>28-32W : T5 2x28W/T8 2x36W           |

### Ordering Data

| Model                  | Watt   |
|------------------------|--------|
| LRLL105/2S/CT-XXLED-T8 | 14-18W |
| LRLL105/2L/CT-XXLED-T8 | 28-32W |



### Related Products



LED-T8

