

LED Canopy / Tunnel



TIS CAL510

Application

Canopy is designed to illuminate tunnels, underpasses, warehouses, garages, indoor gymnasiums, recreational and competition sport fields, etc.

Specification

Housing	Die-cast aluminium
Front Cover	Clear toughened glass
Finishing	Powder coated in black
Lens	Acrylic (PMMA)
Gasket	Silicone rubber
Dimension	250x500x180 mm.
Mounting	Surface
Power	35/55/70W
Light Source	LED Module
Colour Temperature	3000/4000/5700K
Luminaire Output	35W : 4900 lm (55 degree) 35W : 4550 lm (90 degree) 55W : 7700 lm (55 degree) 55W : 7150 lm (90 degree) 70W : 9800 lm (55 degree) 70W : 9100 lm (90 degree)
Beam Angle	55/90 degree
Control Gear	Built-in driver
Dimming Method	1-10V (optional)
Power Supply	220-240VAC, 50Hz
Power Factor	>0.95
IP Rating	66
Luminaire Lifetime	50,000 hrs.
Equivalent	35W : MH 70W 55W : MH 100W 70W : MH 150W

Ordering Data

Model	Watt
CAL510-35LED	35W
CAL510-55LED	55W
CAL510-70LED	70W

