## **ESLL150W/SOLAR/REMOTE/POLE**

## Application

Village Road, Playground, Alley

## Specification

Housing

Die-casting Aluminium

Structure

LED Streetlight with Battery Build-in Solar panel is installed separately

Led Chip High Power " EPISTAR" 60 pcs

**Description** Controlled working by Ambient Light

Can be adjusted brightness by remote

controller

Can be setted working hours 3H 5H 8H Brightness will be reduced according to remaining capacitly of battery and maintain at 30% until dawn

Pole 6 meters supplied in complete set (Cannot be used with other poles)

Finishing Coated in Grey

**Charger** Controlled by Battery Management

System (BMS)

**Solar Cell** Monocrystalline Solar Panel 6V 60W

 
 Battery
 LifePO4 Battery

 Lens
 Oval Len 70-135 degree

 Dimension
 520x210x90 mm for streetlight 670x640x25 mm for solar panel

 Mounting
 Side entry pole or bracket arm

Power 150W
Light Source LED Module
Colour Temperature 5000 K

 Colour Temperature
 6500 K

 Luminaire Output
 4500 Im

 Control Gear
 Charger Build-in

 Power Supply
 Battery 3.2V 66Ah

 Standard
 MIT6611000618

 IP Rating
 IP65

IP Rating
Ordering Data

Model	Watt
LUMAX # ESLL150W/GR-60LED/6.5K-	150W
XSXD/R+POLE6M	







