

Application

Recessed downlight is designed to use for office buildings, shopping centers, convenience stores, modern trade stores, discount stores, hotels, resturants, residences, recreation centers, museums.etc.

Specification

Housing Die-cast aluminium

Description Primary reflector: Vacuum aluminum

> plating PC/ High quality lens 4 different secondary reflectors are available for various applications WR (front reflector white) BR (front reflector black) MB (front reflector mirror black) MI (front reflector mirror chrome)

Finishing Powder coated in white

Mounting Recessed Power 14/18W **Light Source** LED COB **Colour Temperature** 3000K/4000K/5000K CRI >90/ >90/ >80

Lamp Output 14W: 1540/1660/1805 lm

18W: 1980/2134/2320 lm 14W: 1460/1562/1671 Im *

18W: 1808/1934/2069 Im *

Beam Angle 15/18/26/38/55 Degree

UGR <19


Luminaire Output


Control Gear Separate Driver **Power Supply** 220-240VAC,50Hz


Power Factor >0.9 **Insulation Class IP Rating** 20 **Luminaire Lifetime** 40,000 hrs Remarks * Value at 38 Degree

Ordering Data

Model	Watt
RAL86J/MI/WH-14LED	14W
RAL86J/MI/WH-18LED	18W









2.0 m







Related Products





